


PRODUCT LIST



Name PURO CONTOUR PENTAGON 600

Type pendent lamp

ID PC1135



Description Puro is a boldly minimalistic variation on atmospheric pendant lights. Inspiration for the collection and its name come from the Spanish word for "cigar", which also means "pure" and is a reference to the composition's clean lines. The diffused glow of the tubes to elicit a dynamic ambience, while the alternating gloss and matte finishes provide a degree of provocation. Puro offers atmospheric room lighting as well as lighting for offices, hospitality interiors, boutiques, showrooms and private dining areas.

Technical description

Glass Colour

| | | |
|---------------------|---|---------|
| triplex opal | A | CGC39 |
| dark grey - opaline | B | CGC1507 |

Glass surface

| | | |
|-------------------------------|---|---------|
| acid-etched both side surface | A | CGSU881 |
|-------------------------------|---|---------|

Body finish

| | | |
|-----------------------------------|---|--------|
| iron - black matte powder coating | A | CCS846 |
| iron - white matte powder coating | A | CCS845 |

Canopy finish

| | | |
|-----------------------------------|---|---------|
| iron - black matte powder coating | A | CCSC619 |
| iron - white matte powder coating | A | CCSC618 |

Connection method

| | | |
|------------------|---|---------|
| BROKIS connector | A | CCM1019 |
|------------------|---|---------|

Cable colour

| | | |
|-----------------------|---|---------|
| textile cable - black | A | CECL519 |
| textile cable - white | A | CECL521 |

LED Source

| | | |
|--|---|----------|
| 600mm 24V, LED, 9.5W, 2700K, 547lm, RA80+, DIM | A | LEDS1926 |
| 600mm 24V, LED, 9.5W, 4000K, 672lm, RA80+, DIM | A | LEDS1927 |
| 600mm 24V, LED, 9.5W, 5000K, 711lm, RA80+, DIM | A | LEDS1928 |

Dimmable version

| | | |
|------------------------------------|---|----------|
| non-dimmable version | A | CEDV1457 |
| RF system - remote control version | A | CEDV1461 |
| PWM signal | A | CEDV1459 |
| 1-10V | A | CEDV1460 |
| DALI version | A | CEDV1458 |
| AC phase-cut | A | CEDV1730 |